

## Panel P11/N Ultra-Max user manual

1. Place the device on a conference table, desk, floor or hang on the wall. Point the jammer with the camouflage fabric towards the person at whom you want to jamm the voice recorder.

The recommended distance of P11 Panel from the interlocutor whose recording device will be jammed is 1 to 5m.

The device's effectiveness is affected by:

the placement of P11 Panel and the volume of the protected person's voice - weaker and quieter voice = better efficiency.



### 2. Turning on the device

a) Connect the AC adapter to the power socket on the side of the device.

b) Turning the device on and off is done by pressing the green button on the remote control. Turning on the device is signaled by a double blink of the red indicator diode in the ruler, off - the LED will blink once.

### 5. Safety conditions:

a) Do not open the device, breaking the seals will immediately void the warranty.

b) Keep away from the machine during work at a distance of less than 0.5 m.

c) Do not cover the jammer with any objects from the side of masking material, it may result in inefficiency and serious failure of the device

d) Pregnant women and animals should not be within the device's range during operation.

### 6. Service and repair

The manufacturer undertakes to maintain a 24 months warranty

The warranty period may be extended with a special order.

### 7. Characteristics

- type of work: Proprietary software for generating digital jamming signal.

- quiet operation - does not emit an audible and bothersome sound

- remote radio on / off with the remote control

- discreet signaling of switching the device on and off

- simple handling and operation.

### 8. Basic technical parameters

- maximum range: depending on the type of voice recorder, wiretapping from the 1st to about 10 meters

- directionality of Panel P11/N work in horizontal and vertical 90 ° planes

- power supply - 110-230V AC adapter

- maximum continuous operating time 3 hours, break time 30 minutes.

- radio remote control - on and off, working range about 20 m.

- radio remote control: operating frequency 433.92 MHz ISM band

- weight: 2 kg, operating range from 0 ° to + 40 ° C (32-104 Fahrenheit)

- size: length 43cm, height 33cm, thickness 3.5cm

- warranty: 24 months

