

AHD-TR10

Digital Wireless Transmitter and Receiver

Features

- AHD high-resolution digital wireless secure transmission/reception.
- Suitable for private use where cabling is unsuitable or internet access is unavailable.
- Lightweight, compact, and easy to use. No complex setup required!
- TX/RX frequency settings utilize automatic codec for secure operation.
- Built-in high-capacity battery for portability. Extended operation with applied AC power.
- Compatible with the BU-18AHD Camera or other compatible AHD cameras.
- Signal reception compatible with the PV-1000AHD or other compatible AHD DVR for recording and archiving.
- Tested transmission range: 500 meters in an open line of sight!



Specifications

Q-AHD-TX10

| | |
|---------------------------|--|
| Internal Module | Internal 2.4G Digital Module |
| Output Power | 10-11dBm / Standard |
| T / R Frequency | 2408 - 2478Mhz |
| Tx Channel | 19 Channels |
| Dynamic Rate | Around 200/s |
| RF Band Width | 12 Mbps |
| Modulation | QPSK /16QAM |
| Latency | Including AHD Conversion. Overall Latency Around 100ms |
| TX Video in Signal Format | AHD @1080P/720P |
| ANT Gain | 3dB |
| Working Range | Open Terrain 620 meters |
| Power Input | DC 5V |
| Power Consumption | External Camera: 900mA-950mA |
| | No Camera: 370-400mA |
| | Transmitting Static Images: 940-1050mA |
| | Transmitting Dynamic Images: 1.2A-1.4A |
| Charging Time | 1.5A 4000mA Battery 4H |
| Battery Input | DC 3.7V / 4000 mA LI battery |
| Battery Lifetime | Continuous TX:220Min |
| Dimension | 88 x 25 x 23mm |
| Weight | 95g |


Q-AHD-RX10

| | |
|-------------------------------|--------------------------------|
| Internal Module | Internal 2.4G Digital Module |
| T / R Frequency | 2408 - 2478Mhz |
| Rx Channel | 19 Channels |
| RX Video Output Signal Format | AHD @1080P/720P |
| ANT Gain | 3dB |
| Video Output Impedance | 75Ω, Typ |
| Power Input | DC 5V |
| Power Consumption | No TV Output: 370mA-400mA |
| | Transmitting images: 450-500mA |
| Charging Time | 1.5A 4000mA Battery 4H |
| Battery Input | DC 3.7V / 4000 mA LI Battery |
| Battery Lifetime | Continuous TX: 450 Min |
| Dimension | 88 x 25 x 23mm |
| Weight | 95g |


User Manual




Antenna




S-PJ-BNC-F *2



S-PJ-AHD-PJ





USB-DC Cable *2




DC 5V Charger *2



Optional Accessories



PV-1000AHD



S-PJ-DC12V-BNC

*Specification are subject to change without prior notice.

※This product is for Law Enforcement and Home Security Use Only!

CE/FCC Certified

Contact Us:

Tel. +385 51 673 400

Fax. +385 51 671 542

Mail:

info@spyshopeurope.com

sales@spyshopeurope.com

Beling d.o.o.

Franje Čandeka 23B

51000 Rijeka, Croatia

VAT No. HR 80249393012