

■ Jammer of microphones and audio recorders

SEL ULTRA SPEAKER

SEL ULTRA SPEAKER is a modern microphone jammer, which is using high-quality ultrasonic transducers controlled by a microprocessor, integrated into a common ceiling speaker case and intended for installation above desks and tables in meeting rooms.



Device is an effective jamming device, producing a complex jamming signal in the ultrasonic band above the point of human hearing. A system of high-quality ultrasonic transducers controlled by a microprocessor that achieves the best possible jamming efficiency and makes any recorded conversation impossible to playback. Due to jammers ceiling mounting position, a multipath propagation effect is created, which reflects the generated noise from surfaces and items, further increasing the suppression area and efficiency.

Features

- Type of work: proprietary software for generating digital ultrasonic jamming signal;
- Easy to use control: can be turned on/off via presence of power in the power supply line;
- The radio remote control turns jamming noise off and on;
- Quiet operation - does not emit an audible and troublesome sound;
- Simple operation and use;
- Easy mounting spring brackets.

Application

Device effectively blocks wiretaps, voice recording and microphones in a distance of ~ 3 meters such as:

- microphones in cell phones;
- digital recorders of the sound with the built-in microphone or the microphone on the cable;
- professional digital dictaphones of the type : EDIC-the mini, Gnome, Olympus, Papyrus...;
- dictaphones built-in in Smartphones of the type: **iPHONE 15 PRO MAX**, HTC, SONY , LG, SAMSUNG...;
- radio microphones, microphones of recorders audio-the video;
- microphones of cameras, bugging microphones;
- professional dictaphones hidden in cards to ATMs.



Specifications

Max range: depending on the type of microphone	~ 3 m
Directionality	horizontal plane 120°
Power supply	the power adapter 15 V/110-230 V
Maximum continuous operating time	4-5 hours, break time 30 minutes
Remote control	switching on/off, the range ~ 20 meters
Wireless remote control	work frequency 433.92 MHz in the ISM band
Mounting hole diameter	190mm, mounting template included
Operating temperature	0° ... +40°C (32-104 Fahrenheit)
Set includes	jammer, power adapter, remote control (2pcs)